


MAURER Retractable Bumps

The constraint-free modular expansion Joint for railway bridges




Product description:

The occurring movement between superstructure and abutment leads to additional track-tension on train bridges and transmit it over to the fortifications. Introducing the retractable bumps, a crossing system which enables gaps between the individual bumps do not exceed the legal limit on the one hand and absorbs possible movement of the structures without any damage on the other hand. This system evolved the elastic forced control in a way that makes it able to face every challenge of train traffic. The retractable bump is bound to the structure monolithically via encapsulation after aligning them in the intended recesses on site.

Benefits:

- standardized for pathways up to 1600mm, axle loads of 250kN and speeds up to 300km/h
- permanent, water-proof and constraint-free
- can take torsion and safe against lifting-off
- no disturbances in comfort
- simple to install
- easy to inspect and maintain

forces in motion





 18. FEBRUAR
DER EISENBAHN INGENIEUR
 INTERNATIONALE FACHZEITSCHRIFT FÜR SCHIENENVERKEHR & TECHNIK

Euro 28,10 | February 2022 **02 | 22**

NBS Wendlingen – Ulm –
 Quality Control of the Slab Track through inertial metrology

KIB –
 Groundscrews as an low-emission alternative

Battery-powered Trains –
 First 50Hz-fast charging Station for trains

Overhead lines –
 Solution for efficient bird protection

Superstructure –
 Report of the 4. rail construction forum



13. Civil Engineering Congress
 16. - 17. February 2022
 in Dresden
 und im Livestream

Sustainable foundations without concrete

Ground screws as a modern option for low-emission and dismantle-able foundations - a description of the applications in the KIB



Graphic 1: ground screws

Source: T. Molter

TRISTAN MOLTER | IAN KRUKOW | JOHANNES DILLIG

Foundations so far are known almost exclusively as concrete. Ground screws, however, are rising in importance by the day because they are so much quicker to install. They are also easy to uninstall without any problems which makes them quite sustainable. As of right now, ground screws are used for dynamic loads, such as noise barriers.

The beginnings

Foundations have been known to be made from concrete traditionally. No matter if its a small shed or a big house everyone thinks of strip footings or surface foundations made out of concrete. In the past years there has been an uprising of alternatives in fortifications and footings (e.g. garden sheds). Those footings have a steel shell with sheet metal welded onto because of which the shell can drilled into the ground flawlessly. This system is quite similar to drywall screws which also has a kind of shell, as shown in Graphic 1. This construction has been developed step-by-step. The core principle originated a thousand years ago called "pile foundation" and has been developed to the point to which ground

screws have become a safe solution for foundations. They can withstand heavy loads as much as traditional concrete foundations could.

Another benefit of ground screws is that no digging is necessary and by extension no transport of spoil is required. (Un-)Installation does not require any form of Terra-forming. For those reasons ground screws are very eco-friendly and sustainable. And despite all that, the installation time is also much shorter compared to traditional foundations. It can even be as short as several minutes.

Ground screws role in Deutsche Bahn's constructive engineering

Deutsche Bahn AG (DB) wanted to take advantage of the benefits of ground screws as well. But for that to happen an admission by the Federal Train Authority (EBA) is needed. First efforts have been made to get an admission for static purposes with the intention to implement the ground screws in projects of constructive engineering (KIB) such as train platforms or railings. Those efforts have been initiated by a company called CTS Composite Technologie System GmbH in Geesthacht because they intended to install their products easier and faster. After passing all the tests with flying colors EBA gave out an admission for field-tests. From that point forward a number of project were able to be finished successfully (Graphic 2

and 3).

The further development to dynamic load transfers

The experience with purely statically loaded ground screws lead to dynamic loadings as the self-explanatory next step. In order to deliver proof of the dynamic load transfer capabilities of ground screws, exceptions and assumptions were necessary. To measure the ground screws a standard case of inner city noise barriers was chosen. This covers a vast majority of fields in which the usage of ground screws is applied. As noise protecting element a mix of aluminum cassettes and concrete was used. The standard case and test is taken with current technology. In the beginning the ground screws are treated like a pile driver pipe. To which extend this procedure is accurate remains to be seen until planned tests for train plateaus have taken place in the future. In order for construction companies to remain familiar and comfortable with ground screws without getting used to them first, thoughts went into coming up similarities between ground screws and noise barrier posts. Those posts are usually placed into pile driver pipe with the help of concrete. During the development of ground screws for noise barriers, the top part of the ground screws has been designed like a pile driver pipe so that the conventional method mentioned can still be applied. Alternatively, a second variant has been developed which envisages an adapter



Graphic 2: embankment stairs resting on ground screws

Source: CTS

that can easily be screwed onto the noise barrier posts.

The diameter of the ground screw is smaller than the usual pile driver pipe. To make sure that a high enough margin for the positioning of the post inside of the pipe is provided, the head area of the ground screw is approximating into a rectangular cross section. This leads to a transition from a circular to a rectangular cross section with spikes that will prove crucial for measuring processes.

A three-dimensional CAD-model of the b|bW head is transitioned to a area-model with finite

elements that provides the tensions necessary. As a result of trains passing by, pressure-suction-waves with a high amount of load changes are created. Those are taken into account as quasi-static loads at the limit state of loading capacity. Additionally, proof of the longevity are required to rule out long-term failure of the constructions. Graphic 4 shows the distribution of tension spikes for both cases with which the capacity limit of the transformed pipe can be determined.


As an alternative to clamping the post infa the pile driver b|bW a screw terminal with a

base is provided. The design is carried out through a standard procedure. A cleat is taking care of the thrust transmission which will also be put into concrete. Nevertheless, the total amount of concrete used is significantly lower compared to the first method because only the cleat will be clamped and not the entire post. Additionally, the work hardening of the pipe will not be necessary for the process due to accurate positioning made possible by slotted holes in the base. However, because the base has to be screwed on the outside of the pipes diameter, it is quite large. That's why additional ribs are



Graphic 3: platform system and temporary train platform

Source: CTS



Graphic 4: FEM-Model of the ground screws' adapter

Source: Dillig Ingenieure

mandatory in order to be able to take the bending momentum.

To test the theory out in practice, ground screws have been tested on a railway and proving grounds with matching soils. Table 1 shows the concept of the experiment. At the railway in Laufach tests have been made with trains as well as proof loads for pressure and horizontal stress (Graphic 5). At the proving grounds, cyclic tests alongside statically combined proof loads (traction and pressure) have been taken on different soils.

Construction noise and vibrations

The construction of noise barrier posts at railway facilities is so far done through rammed tubular steel posts. These are installed with the help of high-frequency vibrating pile drivers mounted onto an excavator. This results in a lot of noise and vibrations for the residents leading to a lower acceptance by them. That could become the cause of delays when trying to realize a project due to construction freezes.

During the test installation of the ground screws (Graphic 5) sound levels as well as vibration levels have been measured and compared to rammed tubular steel posts.

The temporary results show that the installation of a ground screw is significantly more quiet than the ramming of a steel post. The created sound level during the installation of a ground

screw is around 9 dB(A) lower than the steel post rammed into the same location. A realistic combination of excavators with equipment and mounted tools needed for each method have been used during the test. The test installation took place in non-cohesive soils. A temporary comparison of the two sound levels in accordance with AVV Baulärm leads to a reduction of the minimum of required distance for construction from around 64 m (rammed posts) to only 24 m (ground screws). As a result, the acceptance by residents for noise barrier constructions will rise and construction freezes will be reduced.

The vibrations created during the installation of ground screws can be lowered by a multiple (compared to rammed posts). Damage risks in towns, cities or other construction sites with many adjacent buildings can be reduced as well. According to the temporary results, the vibrations emitted by installing ground screws are way below the

threshold necessary to be damaging to adjacent structures (2,50 [mm/s] at the base) - whereas the rammed alternative would have exceeded these thresholds and limits by DIN 4150-2 by a landslide. Graphic 6 shows this in an exemplary way for a distance of 30 m to the installation point.

Conclusion

Ground screws are becoming more and more important. The benefits are the independence from the weather, that no drying or hardening rests are needed as well as being able to cut the excavation work - which by extension also cuts the transport of dug up soil. Additionally, ground screws are precisely predictable under static and also dynamic circumstances. Construction noise and vibrations are reduced significantly compared to traditional methods. Minimal de-installation costs support the longevity and sustainability of projects using ground screws as a base and they are also more eco-friendly due to

the lack of excavation and soil destruction needed. The last point on its own would already more than enough to show the improvement ground screws provide in this field.

A lot more possible fields of usage for ground screws will be experimented with in the near future leading to an even higher acceptance in the industry, further underlining the long-term potential of ground screws.

soil type		non-cohesive soil	cohesive soil
testing location		Laufach No. 5 (KRB 523)	Laufach No. 4 (KRB 521)
static PB combined	pressure (axial to post axis)	1x	1x
	horizontal (transverse to post axis)	1x	1x
static PB extra	traction (axial to post axis) - pile driver pipe	-	1x
	traction (axial to post axis) - KRINNER ground screw	-	1x
testing location / testing grounds (e.g. Straßkirchen or similar)		testing grounds?	testing grounds KRINNER
cyclic PB horizontal	1. preliminary tests static PB horizontal	1x	1x
	2. cyclic PB (100.000 load cycles)	1x	1x
	3. post-cyclic static PB horizontal	1x	1x

Table 1: concept proof loads

Source: Boley Geotechnik



Graphic 5: test installation of ground screws

Source: Krinner

KRINNER Ground Screws
efficient - concrete free - durable

mit **EBA** Zulassung

PREMIUM PARTNER

KRINNER Das Schraubfundament

Make an appointment now


CONSULTING | DELIVERY | INSTALLATION

Quick, safe and instantly usable: KRINNER Ground Screws make precise constructions without two-way technology or shutting down the railways possible. This saves a significant amount of time and shortens construction times to a minimum.

Fields of application:

- embankment stairs
- signals
- lamp posts
- railings
- pedestal
- fences
- noise barriers

Contact us
Mercatorstr. 43
21502 Geesthacht
Phone: +49 4152 8885-0
E-Mail: info@ctscom.de
Internet: www.ctscom.de



Graphic 6: vibration velocity in X,Y,Z - directions [mm/s] (Dilling | Prinz Ingenieurteam)

Source: Krinner

VDE Committee
Constructive Engineering



Dr.-Eng. Ian Krukow
Structural Engineering
Dilling Ingenieure GmbH, Simmern
ikrukow@dilling.de



Dipl.-Eng. Tristan Molter
Design Responsibility, Bridge Construction &
Circuit Breaker Systems Technology
DB Netz AG, Munich
tristan.molter@deutschebahn.com



Dipl.-Johannes Dilling
CEO
Dilling Ingenieure GmbH, Simmern
j.dilling@dilling.de

WISSEN, WAS BAHNEN BEWEGT

www.eurailpress.de

Eurail press
DVG Media Group

50-Hz-fast charging station for battery-powered trains

As the first quick charging station of its kind, „VOLTAP“ by the Furrer+Frey AG and the Stadtwerke Tübingen GmbH has been taken into operation successfully.

87>:J 6E5: G@9

7hW fZwCfS' S V dS'1 Sk [Vgefdk [e TWWf] Y Xh fZwa Ya' Y Wa'gfa' e S V` W [hWf]a' e' fZwWwaxISfWZ fWZ a'a'k /WZ' FWS' fZ'4WSgeWaxISZf Wgbb' Y_ aWf' fS' e i [fZ fSf]a' TSfWfW eW e fa TWZwWgfdWi Sk aX YWf] Y dV aX YSe bai WfW fS' eZ : ai WfW fZaeWS] Wa' kS_ [adchWa XcZ 3f fZwS_ Wf_ WZwWgWf]a' aXW_ aT]f]k [e dS]eM fZW cgWf]a' aX dWZSf] Y ZSe fa TMS] W Se i WZ fZW_ aef [badS' f bSf eZag'V TWfa gf]f] W fZwW]e] Y ahMSbe aXfZWf a XWf] adWf]a dWgW]aefeSe_ gZSebae]TW

FISd] YefgSf]a'

3Tagf XgdKW]eSya fZwW]f fZwW]f ha]Uw]i WfW dS]eW W]S V] Y UZSd] YZ XSe]f]g]dW Xid TSfW]Zbai WfW fS' eZ 3 UWSd VhW]f] fZW [Vgefdk aXhW]UW]a' Uf] [YfZWSbbdSZS] W Lag'V TWaW Z'fZaeWZai WfW i WfW]S] Y fa [La_ bS]f]TW]SeS Vdag'feTW WfW fZwW]SfW La_ bS [WZ fZwCfS' eTk EISW]f] ag'V` af ZSHW TWW STWfa TWUZSdW Tk S UZSd] Y eSf]a' _ S gXUfgdW Tk E]W]We Xid W]S_ bW]f; f i Se aThagefZSf fZwCfS' [Vgefdk ZSV fa Va TWfW]ZS' fZwCfS' [Vgefdk V]V La' Uf] [Y UZSd] Y eSf]a' e S V La_ bS]f]f]k [egW]b]qad fa fZW W]Z;` fZW WWS]a]abW]S]a' TW W fZwV]e]a]S]f]a' aXf]d] ; Vgefdk /H64f fZwFG 4W]f] i fZwFG 6dW]W S V afZw]e]S] W]a' W]e U]S]f]W]S La_ _ a' Ychag' V i Z]UZ 'SV fa eW]MS' S]d]W] W]e aX]b]S]e_ W]e]f] fZwW]W aX]TS]f]W]Zbai WfW fS' e fZSf ZSV fa TW S]aW]T]Z

4ag' VSkLa' V]f]a' e

;f i Se aThage Xh_ fZw]W]f [Y fZSf fZw]e [fZ Xh_ YSeZbai WfW W]f] W]fa S' S]f]W S]f]hW]W]f] W [e Ya] Y fa TW]S Uaf'k g' W]S]f] [YZ 7hW]k e' YW W]e]d fZSf ZSe fa _ W_ S]W]f] [XSe]f]g]dW]W]Z bS' [Y S V La' d]f]g]f]a' S egXU]W]f] UZSd] YZ [XSe]f]g]dW] ag'V]b]d]h]W]SeS afZw]a]Te]S]U]W]e]d W]W]f] Y fZw_ S]f]W]Z; X]lag' f]S] W]f] fa S]U]ag' f fZSf afZw] Lag' f]q]W] aX]W] eg]T]e]W]f] i Sk W]e []W]k Xid fZw]W]e] [fZw] fZw]a]S' aX]]W]f] Y fZw]LafZ W]XU]W]k Se Z]YZ Se baef]TW]e _ S V]S]adZ

FZ]eS]Y e i [fZ fZw]e]d]S]W]U]f] f]W]W]e aX]hW]U]W] _ S' gXU]fg]d]e fZSf U]S' _ S] [] W]Zw]d]bafW]f]S' Xid d]W]g]W]Zch]g]Y]S]f]W] S]f]hW]W]f] W]Z fZw]S]f]W]Z]bai WfW hW]U]W]f] 9W] S' k i [^ ZSHW]fa TW]b]d]MS]dW Xid fZw]CfS'1 Sk ha'f]SYW ekefW e35 #]H #]f] :] H TW]SgeW]aX]fZw]S' d]S]W]k W]e]f] Y ahW]Z]S]V [W]f] XSe]f]g]U]fg]d]W]a' _ S' k d]S]Ve S' V d]S]f]1 SkeZ fZw]Zag]Y]Zf aX]ge]f] Y fZ]e ha'f]SYW]kefW] fa UZSd]W]Zw]C]S]U]f]a' TS]f]W]W]X]d Xh_ fZw]bai WfW ekefW _ [Y]Zf eW]W aTh]ageZ 4gf fZw]W]S]S]e gegS'k' yef ZSHW "Z 1Zegbb'k _ S] [Y fZw]geW]aX]S' [hW]f]W] Xid fZw]CfS'1 Sk ha'f]SYW]kefW] a' Lag' f]k e]V]W] S' V]S]adZ fZw]egbb'k aX]fZw]hW]U]W]f] [fZ 35 #]H #]f] :] e g' Vag]f]W]k TW]W]U]S' TW]SgeW]fZw]U]gd]W]f] hW]U]W]W]Y VaW] af ZSHW]fa TW]ZS' YW]S]f]S'z 3 ek_ W]f]U]S' a]S]V aX]fZw]ge]f]d]S' fZw]W]Z]SeW] bai W]f] egbb'k i ag'V TW_ S]W]baef]TW]Se i W]Z fZSf [e Vg]W]fa fZw]d]W]f] La'` W]f]a' aX]S' e]f] Y]W]Z bZSeW]a]S]M [] V]S' f]S]f] Xid W]S_ b]W]f] [fZ S' fZd]W]Z bZSeW]bai W]f] egbb'k S]f] Ske d]ag]f]f] Y [S' g' TS]S' U]W' a]S]V [Xid_ aX]S' b]W]e]d] S' U]W' ek_ W]k i Z]UZ fZw] S]S]f] d]ag]f]e [S' ha'f]SYW ek_ W]k [fZw]fZd]W]Z]SeW]bai W]f] egbb'kZ : ai WfW] fZw]f] hW]f]W]f] Se Xag' V fa TW]Zw] aef Uaf'k bS]f [fZw] W]f]Y aX] S' UZSd] Y [XSe]f]g]d]W] fZw]U]SgeW]aX]fZw]CfS' TS]U]e aX] [hW]f]W]e S]d]W]a]f]W] [ekefW] S]f]U]S' d]S]e]a' e S' V i [^ TW]hag]YZ]k W]b]S]f] W]f] fZw]W]a' ai [YZ

EkefW]Z]MS]W] V]S] TS]U]e aX] [hW]f]W]e 7XU]W]f] [hW]f]W]e S]d]W]W]b]W]e]h]W] 5g]f]f] Y ag]f [hW]f]W]e i ag'V_ W]S' S' Y]d]S]f] bafW]f]S' [Uaf]Z eS]h] Y Tgf i ag'V Stea _ W]S' d]W]k] Y a' fZw] Lag' f]q]W]y X]W]g]W]U]Z fZw]Se]W]e] La' Uf] [Y ha'f]SYW]ek_ W]k i [^ TW]a]TW]f] fa S' e]MS]S]f]W] S]d]U]W]f] aef aX]fZw]f] hW]f]W]e S]d]W]a' k S bS]f] aX]S' La_ b]W]f] S' V i [W]f] ekefW] i Z]UZ La' e]f]e aX] _ g]f]Z]b]Z]SeW] [b]g]Z' S' V _ a' aZ]b]Z]SeW] ag]f]b]g]f] f]S' e]X]d] W]f] U]a]a'f] Y fW]Z a'a'k Se i W] Se La' f]d]a' W]eZ 7hW] fZw]geS]Y]W]aX] Z]Y]Z]k]Z]MS]T]W] La_ ba' W]f]e i ag'V g' S]h]a]V]S]T]k egX]W] Xh_ Z]Y]Z]W]f] a]e]e]W]S' V' ai W]f]d]MS]f]f]k L]ampared to a system consisting of only one single transformer. Not only would the no-load losses, that could be quite significant for a train charging station, play a part in the losses but also the losses occurring during the loading process because the straight effects of all the single parts have to be multiplied. If we calculate with a straight effect of 98,8% for both transformers including the necessary ancillary units with a straight effect of 95%, a result for the process-chain "input transformer - inverter - output transformer" a total straight the

effect of 0,988 x 0,95 x 0,988 = 0,927 = 92,7% would be the result. This would mean that 7,3% of energy are lost in the form of warmth. Because a 50-Hz-station only needs a single transformer its loss of 1,2% would be significantly lower. Spare parts for components of the power are usually easy to come by even a few years after constructing a plant, however, a charging station for trains should still work after decades. This leads to a demanding spare part management which is solely depending on the good will of a small market. Because it seems reasonable to diversify the selection of inverter manufacturers from an economical standpoint, a "spare part zoo" of parts, that are incompatible between each other, is created.