

Technical Data Sheet E Series

Basic Info

KSF E 140x3,6x1600- E76-100 HDG	KSF E 140x3,6x1300- E76-100 HDG
Nominal length (mm)	
1600	1300
Tube diameter (mm)	
139,70	139,70
Weight (kg)	
17,90	14,70
Item number	
A0382	A0380

Construction

- Flange: GP240GH
- Coating: Hot-dip galvanized according to DIN EN ISO 1461
- Continuous welded helix

Applications



Accessories



Eccentric Set-E76 / E80 / E90 / E100
Item No. A1129 / A1130 / A1131/ A1127



Reducer E76-E60
Item No. A0847



Reducer E76-E70
Item No. A0846



Cover Plate E76
2mm DC01
Item No. A0003



Hexagon head
screw M12x60 8.8
TZN DIN933
Item No. A0704



Countersunk
screw E76-E100
Item No. A0718



KSF E
140x3,6x1300-
E76-100 HDG



sustainable · durable · revolutionary

Technical Data

	KSF E 140x3,6x1600- E76-100 HDG	KSF E 140x3,6x1300- E76-100 HDG
a Length (mm) (±25 mm)	1620	1320
b Outer diameter (mm)	139,70	139,70
c Inner diameter (mm)	132,50	132,50
d Diameter setting* (mm)	100 90 80 76**	100 90 80 76**
e Depth setting (mm) (±25 mm)	730 775 810 810	565 630 650 650
f Thread	3 x M12	3 x M12
g Pitch circle diameter (mm)	192	192
h Flange outer diameter (mm)	220	220
i Flange thickness (mm)	20	20

* The diameter setting (d) determines the depth setting (e)

**Tip for installation: To adjust the depth setting, it is recommended to fill in ballast or insert an accessory plate

