

Technical Data Sheet G Series

Basic Info

KSF G 68x2,0x650 1xM8 HDG	KSF G 68x2,0x550 1xM8 HDG
Nominal length (mm)	
650	550
Tube diameter (mm)	
68	68
Weight (kg)	
1,90	1,60
Item number	
A0405	A0403

Construction

- Continuous welded helix
- Coating: Hot-dip galvanized according to DIN EN ISO 1461
- Patented conical body forged from a single piece of tubing
- Nut: DIN EN 4023-5

Applications



KSF G 68x2,0x650 1xM8 HDG

Accessories



Screw-in bar long
Item No. A0134

revolutionary · durable · sustainable

Subject to technical changes!

Krinner Schraubfundamente GmbH | Passauer Strasse 55 | D-94342 Strasskirchen

Technical Data

	KSF G 68x2,0x650 1xM8 HDG	KSF G 68x2,0x550 1xM8 HDG
a	Length (mm) (± 20 mm) 650	550
b	Shaft outer diameter (mm) 68	68
c	Inner diameter (mm) 64	64
d	Diameter setting (mm) 62 55,5 50 43 38,5 34	62 55,5 50 43 38,5 34
e	Depth setting (mm) (± 20 mm) 245 260 275 315 370 425	145 160 175 215 270 325
f	Thread 1 x M8	1 x M8

