

## SAMPLE CALCULATION

### MODUL 1 - 18 m<sup>2</sup> 2 LEVEL (36m<sup>2</sup> USE AREA)

Estimation of the foundation system. Please note: this only provides information for an initial estimate or first cost assesment. The planning basis for the execution must be prepared by the commissioned engineer.

### DISCLOSURES AND ASSUMPTIONS MADE

- ✓ Total dead weight approx.. 7,4 t
- ✓ Snow 1, 10 KN/m<sup>2</sup>
- ✓ Wind 0,39 kN/m<sup>2</sup>
- ✓ Traffic load 1,5 kN/m<sup>2</sup> per floor

### CALCULATION

- ✓  $g_k 4,11 \text{ kN/m}^2 \times 1,35 = 5,55 / \text{m}^2$
- ✓  $q_{ks} 1,10 \text{ kN/m}^2 \times 1,50 = 1,65 \text{ kN/m}^2$
- ✓  $q_{kw} 0,39 \text{ kN/m}^2 \times 1,50 = 0,58 \text{ kN/m}^2$
- ✓  $VK 1,50 \text{ kN/m}^2 \times 1,50 = 2,25 \text{ kN/m}^2$  (x2 Level = 4,5kN/m<sup>2</sup>)

DESIGN LOAD 12,28 kN/m<sup>2</sup>

### SIMPLE, SIMILAR LATIN INSTRUCTION

$12,28 \text{ kN/m}^2 \times 18 \text{ m}^2 = 221,04 \text{ kN} / 4 \text{ KSF's} = 55,26 \text{ kN/KSF}$

### RECOMMENDATION

4 Stück KSF V 114 x 5,0 x 2000 PT incl. head and connection set

### INTEGRATION DEPTH

The actual embedment depth/pile length, is determined according to the soil conditions. Screw piles are considered displacement piles according to DIN EN 12699:2015-07. The determination of the load bearing capacity and the design of the screw piles are determined via available static calculations. The internal load bearing capacity and the load tests should be performed on-site.